

# Sparse grids - an approach to reduce the complexity of multiscale simulations

AERC 2018 – Sorrento – Italy

Alexander Rüttgers


German Aerospace Center (DLR)



Knowledge for Tomorrow



# MODELING OF POLYMERIC FLUIDS




Two different modeling approaches:

overview <sup>1</sup>	macroscopic	multiscale
cost	low	high
modeling accuracy	low	high
drawbacks	num. instabilities	


<sup>1</sup> Le Bris and Lelièvre, Multiscale Model & Simul, 2009

# MICROSCALE MODELING



- Position vector  $\mathbf{x}$  in flow space  $\mathcal{O} \subset \mathbb{R}^3$ .
- $\mathbf{q} = (q_1, \dots, q_N)$  in configuration space  $\mathcal{D} \subset \mathbb{R}^{3N}$ .

# MICROSCALE MODELING



- Position vector  $\mathbf{x}$  in flow space  $\mathcal{O} \subset \mathbb{R}^3$ .
- $\mathbf{q} = (\mathbf{q}_1, \dots, \mathbf{q}_N)$  in configuration space  $\mathcal{D} \subset \mathbb{R}^{3N}$ .


Description of a polymer ensemble

- **Stochastic approach:**<sup>1</sup> random field  $\mathbf{Q} = (\mathbf{Q}_1, \dots, \mathbf{Q}_N)$  with  $\mathbf{Q} : (\mathbf{x}, t) \in \mathcal{O} \times \mathcal{T} \mapsto \mathbf{Q}(\mathbf{x}, t)$  as  $\mathcal{D}$ -valued random variable.

---

<sup>1</sup>Laso and Öttinger, JNNFM, 1993

# MICROSCALE MODELING



- Position vector  $\mathbf{x}$  in flow space  $\mathcal{O} \subset \mathbb{R}^3$ .
- $\mathbf{q} = (\mathbf{q}_1, \dots, \mathbf{q}_N)$  in configuration space  $\mathcal{D} \subset \mathbb{R}^{3N}$ .

Description of a polymer ensemble

- **Stochastic approach:**<sup>1</sup> random field  $\mathbf{Q} = (\mathbf{Q}_1, \dots, \mathbf{Q}_N)$  with  $\mathbf{Q} : (\mathbf{x}, t) \in \mathcal{O} \times \mathcal{T} \mapsto \mathbf{Q}(\mathbf{x}, t)$  as  $\mathcal{D}$ -valued random variable.
- **Fokker-Planck ansatz:**<sup>2</sup> probability density function of field  $\mathbf{Q}$ 
  - $\psi : (\mathbf{x}, \mathbf{q}, t) \in \mathcal{O} \times \mathcal{D} \times \mathcal{T} \subset \mathbb{R}^{3N+4} \mapsto \psi(\mathbf{x}, \mathbf{q}, t) \in \mathbb{R}^+$ .
  - $\int_{\mathcal{D}} \psi(\mathbf{x}, \mathbf{q}, t) d\mathbf{q} = 1$  for all  $(\mathbf{x}, t) \in \mathcal{O} \times \mathcal{T}$ .

<sup>1</sup>Laso and Öttinger, JNNFM, 1993 , <sup>2</sup>Lozinski and Chauvière, J Comp Phys, 2003

# STOCHASTIC MULTISCALE SYSTEM

$$\frac{D\mathbf{U}(\mathbf{x}, t)}{Dt} = -\nabla P(\mathbf{x}, t) + \frac{\beta}{Re} \Delta \mathbf{U}(\mathbf{x}, t) + \frac{1}{Re} \nabla \cdot \boldsymbol{\tau}_p(\mathbf{x}, t) \quad (1)$$

$$\nabla \cdot \mathbf{U}(\mathbf{x}, t) = 0 \quad (2)$$

$$d\mathbf{Q}(\mathbf{x}, t) = \left[ -\mathbf{U}(\mathbf{x}, t) \nabla \mathbf{Q}(\mathbf{x}, t) + (\nabla \mathbf{U}(\mathbf{x}, t))^T \mathbf{Q}(\mathbf{x}, t) - \frac{1}{4De} \mathbf{A} \cdot \mathbf{F}(\mathbf{Q}(\mathbf{x}, t)) \right] dt + \sigma d\mathbf{W}(t) \quad (3)$$

$$\boldsymbol{\tau}_p(\mathbf{x}, t) = C \sum_{i=1}^N (\mathbb{E}[\mathbf{Q}_i(\mathbf{x}, t) \otimes \mathbf{F}(\mathbf{Q}_i(\mathbf{x}, t))] - \mathbf{Id}) . \quad (4)$$

for the unknown random fields  $\mathbf{U}$ ,  $P$ ,  $\mathbf{Q}$ ,  $\boldsymbol{\tau}_p$ ,  
dimensionless parameters  $De, Re, \beta, \sigma \in \mathbb{R}^+$   
+ initial and boundary conditions.

(1)+(2) Navier-Stokes equations (macroscopic)

(3) Stochastic PDE (microscopic)

(4) upscaling from micro- to macroscopic scale

# 3D CONTRACTION FLOW

## For high Deborah number flows

- large corner vortices occur
- streamline divergence




FIGURE: Visualization of contraction flow experiment<sup>1</sup> with  $Re = 2.37$ ,  $De = 174$

---

<sup>1</sup>Sousa, Coelho, Oliveira and Alves, JNNFM, 2011

# 3D SIMULATION RESULTS<sup>1</sup>

- 8 multiscale simulations.

Simulation parameters	
Deborah number $De$	24.1, 108, 157
spring model	FENE chain
spring segments $N$	1, 3, 5
resolution $M_g$	$380 \times 64 \times 64$
samples per cell $M_s$	1200

---

<sup>1</sup>published in Griebel and R., JNNFM, 2014



# 3D SIMULATION RESULTS<sup>1</sup>

- 8 multiscale simulations.
- All elastic effects reproduced in simulation.
- No stability issues occurred.
- Results correspond with experimental measurements.

Simulation parameters	
Deborah number $De$	24.1, 108, 157
spring model	FENE chain
spring segments $N$	1, 3, 5
resolution $M_g$	$380 \times 64 \times 64$
samples per cell $M_s$	1200




FIGURE: Simulation of 5-segment chain with  $De = 157$ .

<sup>1</sup>published in Griebel and R., JNNFM, 2014

# 3D SIMULATION RESULTS<sup>1</sup>

- 8 multiscale simulations.
- All elastic effects reproduced in simulation.
- No stability issues occurred.
- Results correspond with experimental measurements.

Simulation parameters	
Deborah number $De$	24.1, 108, 157
spring model	FENE chain
spring segments $N$	1, 3, 5
resolution $M_g$	$380 \times 64 \times 64$
samples per cell $M_s$	1200




FIGURE: Simulation of 5-segment chain with  $De = 157$ .

<sup>1</sup>published in Griebel and R., JNNFM, 2014

# COMPLEXITY OF MULTISCALE SIMULATIONS

- $M_g$  grid cells in space,
- $M_s$  samples per grid cell,
- spring model with  $N$  segments.

# COMPLEXITY OF MULTISCALE SIMULATIONS

- $M_g$  grid cells in space,
- $M_s$  samples per grid cell,
- spring model with  $N$  segments.

**MACROSCALE** storage size of order  $\mathcal{O}(M_g)$  in each time step.

**MICROSCALE** Complexity of discrete samples of order  $\mathcal{O}(M_g \cdot M_s \cdot N)$  per time step.

# COMPLEXITY OF MULTISCALE SIMULATIONS

- $M_g$  grid cells in space,
- $M_s$  samples per grid cell,
- spring model with  $N$  segments.

**MACROSCALE** storage size of order  $\mathcal{O}(M_g)$  in each time step.

**MICROSCALE** Complexity of discrete samples of order  $\mathcal{O}(M_g \cdot M_s \cdot N)$  per time step.

3D contraction flow	microscale $\mathbf{Q}$
spatial grid $M_g$	$380 \times 64 \times 64$
samples per cell $M_s$	1200
spring segments $N$	5
total samples	$1.87 \cdot 10^9$
sample dimensionality	15-dim
storage	208 GB
comput. time (256 CPUs)	7-8 weeks

# COMPLEXITY OF MULTISCALE SIMULATIONS

- $M_g$  grid cells in space,
- $M_s$  samples per grid cell,
- spring model with  $N$  segments.

**MACROSCALE** storage size of order  $\mathcal{O}(M_g)$  in each time step.

**MICROSCALE** Complexity of discrete samples of order  $\mathcal{O}(M_g \cdot M_s \cdot N)$  per time step.

3D contraction flow	microscale $\mathbf{Q}$
spatial grid $M_g$	$380 \times 64 \times 64$
samples per cell $M_s$	1200
spring segments $N$	5
total samples	$1.87 \cdot 10^9$
sample dimensionality	15-dim
storage	208 GB
comput. time (256 CPUs)	7-8 weeks

## Solution approach

- 1 Parallelization.
- 2 Model complexity reduction.

## Sparse grids and combination technique<sup>1,2</sup>

- Approximation of full grid solution  $\mathbf{u}_I \in V_I$  as a **combination of coarse full grid solutions**  $\mathbf{u}_m \in V_m$ .
- Multi-indices  $\mathbf{m}, \mathbf{l} \in \mathcal{I} \subset \mathbb{N}^d$  denote discretization accuracy.
- Approach bases on multivariate extrapolation.




FIGURE: Classical 2d combination technique.

<sup>1</sup>Griebel, Schneider, Zenger, Iterative Meth Lin Alg, 1992

<sup>2</sup>Bungartz, Griebel, R de, Comput Meth Appl Mech Eng, 1994

## Sparse grids and combination technique<sup>1,2</sup>

- Approximation of full grid solution  $\mathbf{u}_I \in V_I$  as a **combination of coarse full grid solutions**  $\mathbf{u}_m \in V_m$ .
- Multi-indices  $\mathbf{m}, \mathbf{l} \in \mathcal{I} \subset \mathbb{N}^d$  denote discretization accuracy.
- Approach bases on multivariate extrapolation.
- Combination technique is intrinsically parallel.
- Existing multiscale solver can be **reused**.





FIGURE: Classical 2d combination technique.

<sup>1</sup>Griebel, Schneider, Zenger, Iterative Meth Lin Alg, 1992

<sup>2</sup>Bungartz, Griebel, R de, Comput Meth Appl Mech Eng, 1994




# MULTISCALE MODEL DIMENSIONS




Discretization and modeling grid

# MULTISCALE MODEL DIMENSIONS




Discretization and modeling grid

# MULTISCALE MODEL DIMENSIONS



Discretization and modeling grid

# MULTISCALE MODEL DIMENSIONS



Discretization and modeling grid

## QUESTION


How can an appropriate index set  $\mathcal{I}$  be generated?

## QUESTION

How can an appropriate index set  $\mathcal{I}$  be generated?

### Adaptive refinement of the $d$ dimensions<sup>1,2</sup>


- Start:  $\mathcal{I}^{(1)} = \{1, \dots, 1\} \in \mathbb{N}^d$ .



Example for  $d = 2$ :

Index set  $\mathcal{I}^{(1)} = (1, 1)$

combination coefficient  $d_{(m_1, m_2)}$




<sup>1</sup>Gerstner and Griebel, Numer Algorithm, 1998    <sup>2</sup>Gerstner and Griebel, Comput, 2003

## QUESTION

How can an appropriate index set  $\mathcal{I}$  be generated?

### Adaptive refinement of the $d$ dimensions<sup>1,2</sup>


- Start:  $\mathcal{I}^{(1)} = \{1, \dots, 1\} \in \mathbb{N}^d$ .
- Iteration  $it \rightarrow it + 1$ :
  - Consider cost  $c_{\mathbf{m}}$  and benefit  $b_{\mathbf{m}}$  for all  $\mathbf{m} \in \mathcal{I}^{(it)}$ .
  - Refinement of the space with maximum cost-benefit ratio  $g_{\mathbf{m}}$  in all  $d$  dimensions, if permitted.



<sup>1</sup>Gerstner and Griebel, Numer Algorithm, 1998    <sup>2</sup>Gerstner and Griebel, Comput, 2003

# SIMULATION 1: COUETTE FLOW<sup>1</sup>

- Non-Newtonian fluid in 2D channel:  
velocity field  $\mathbf{u} = (u, v)$ .
- At  $t = 0$  the fluid is at rest.
- Constant shearing with  $\dot{\gamma} = \frac{\partial u}{\partial y} = 1$  for  $t > 0$ .



(a) shear flow ( $t \rightarrow \infty$ )


---

<sup>1</sup>published in R. and Griebel, Applied Mathematics and Computation, 2018




# SIMULATION 1: COUETTE FLOW<sup>1</sup>

- Non-Newtonian fluid in 2D channel:  
velocity field  $\mathbf{u} = (u, v)$ .
- At  $t = 0$  the fluid is at rest.
- Constant shearing with  $\dot{\gamma} = \frac{\partial u}{\partial y} = 1$  for  $t > 0$ .
- Spring model with  $N = 1$  segment.
- **Aim:** Accurate approximation of oscillating velocity component  $u$ .



(a) shear flow ( $t \rightarrow \infty$ )



(b) Evolution at position  $y = 0.5$   
in channel of height 1

<sup>1</sup>published in R. and Griebel, Applied Mathematics and Computation, 2018

## DIMENSION-ADAPTIVE REFINEMENT

- 3 directions of refinement:
  - spatial grid
  - stochastic grid
  - temporal grid
- Initial level  $(1/\Delta y_{m_1}, \text{Samples } m_2, 1/\Delta t_{m_3}) = (2, 256, 16)$ .
- Refinement by a factor of 2 in each level.

# DIMENSION-ADAPTIVE REFINEMENT

- 3 directions of refinement:
  - spatial grid
  - stochastic grid
  - temporal grid
- Initial level  $(1/\Delta y_{m_1}, \text{Samples } m_2, 1/\Delta t_{m_3}) = (2, 256, 16)$ .
- Refinement by a factor of 2 in each level.
- Cost-benefit ratio index  $g_m$  indicates directions of refinement.




FIGURE: Cost-benefit index  $g_{(m_1, m_2, m_3=3)}$  for  $\Delta t_{m_3} = 1/64$

# VISUALIZATION OF THE ALGORITHM





FIGURE: 3D index set  $\mathcal{I}^{(it)}$  in iteration step  $it = 90$ .

# CONVERGENCE OF COMBINATION TECHNIQUE



**FIGURE:** Relative error  $E(u^{C,it}) = \|u^{C,it} - u_{\text{ref}}\|_2 / \|u^{C,it=1} - u_{\text{ref}}\|_2$

# CONVERGENCE OF COMBINATION TECHNIQUE





FIGURE: Relative error  $E(u^{C,it}) = \|u^{C,it} - u_{\text{ref}}\|_2 / \|u^{C,it=1} - u_{\text{ref}}\|_2$

## Error and cost analysis

- Adaptive solution  $u^{C,it=90}$  has similar accuracy as  $u_{7,7,7}$ .
- Complexity of  $u^{C,it=90}$  is  $\approx 10$ -times lower than full grid  $u_{7,7,7}$ .

## SIMULATION 2: 3D EXTENSIONAL FLOW<sup>1</sup>

- Non-Newtonian fluid in steady 3D extensional flow.




(a) extensional flow

---


<sup>1</sup>published in R. and Griebel, Applied Mathematics and Computation, 2018

## SIMULATION 2: 3D EXTENSIONAL FLOW<sup>1</sup>

- Non-Newtonian fluid in steady 3D extensional flow.
- **Aim:** Temporal evolution of stress tensor  $\tau_p$  for nonlinear FENE chain with  $N = 5$  segments.
- $3N + 1$ -dimensional density  $\psi : (\mathbf{q}, t) \in \mathbb{R}^{3N} \times \mathbb{R} \mapsto \psi(\mathbf{q}, t) \in \mathbb{R}^+$ .



(a) extensional flow



(b) 5-segment FENE chain

---

<sup>1</sup>published in R. and Griebel, Applied Mathematics and Computation, 2018



# DIMENSION-ADAPTIVE REFINEMENT

- 3 directions of refinement:
  - stochastic grid
  - temporal grid
  - spring model grid (modeling error)
- Balancing of numerical and modeling errors.

## DIMENSION-ADAPTIVE REFINEMENT

- 3 directions of refinement:
  - stochastic grid
  - temporal grid
  - spring model grid (modeling error)
- Balancing of numerical and modeling errors.
- Initial level (samples  $m_1$ ,  $1/\Delta t_{m_2}$ , segments  $m_3$ ) = (1024, 2, 1).
- **Refinement** by **factor 2** in stochastic/time, **+1** for spring model grid.

# DIMENSION-ADAPTIVE REFINEMENT

- 3 directions of refinement:
  - stochastic grid
  - temporal grid
  - spring model grid (modeling error)
- Balancing of numerical and modeling errors.
- Initial level (samples  $m_1$ ,  $1/\Delta t_{m_2}$ , segments  $m_3$ ) = (1024, 2, 1).
- Refinement by factor 2 in stochastic/time, +1 for spring model grid.
- Cost reduction by factor of 5 compared to a classical full grid.

# DIMENSION-ADAPTIVE REFINEMENT

- 3 directions of refinement:
  - stochastic grid
  - temporal grid
  - spring model grid (modeling error)
- Balancing of numerical and modeling errors.
- Initial level (samples  $m_1$ ,  $1/\Delta t_{m_2}$ , segments  $m_3$ ) = (1024, 2, 1).
- **Refinement** by **factor 2** in stochastic/time, **+1** for spring model grid.
- **Cost reduction by factor of 5** compared to a classical full grid.




FIGURE: Comparison of approximation spaces for  $\tau_{xx}$ .

## Summary

- 1 Reduction of enormous computing time with twofold parallelism:
  - parallelization (*Atacama* cluster 1248 CPUs).
  - sparse grid combination technique.

## Summary

- ① Reduction of enormous computing time with twofold parallelism:
  - parallelization (*Atacama* cluster 1248 CPUs).
  - sparse grid combination technique.
- ② Application of sparse grids for non-Newtonian fluids:
  - Balancing of numerical and modeling errors.
  - Computation effort reduced by up to one order of magnitude.

## Summary

- ① Reduction of enormous computing time with twofold parallelism:
  - parallelization (*Atacama* cluster 1248 CPUs).
  - sparse grid combination technique.
- ② Application of sparse grids for non-Newtonian fluids:
  - Balancing of numerical and modeling errors.
  - Computation effort reduced by up to one order of magnitude.

## References

- M. Griebel, A. Rüttgers  
**Multiscale simulations of 3D viscoelastic flows in a square-square contraction**  
*J Non-Newton Fluid Mech*, 205:41-63, 2014
- A. Rüttgers, M. Griebel  
**Multiscale simulation of polymeric fluids using the sparse grid combination technique**  
*Appl Math & Comput*, 319:425-443, 2018

Thank you for your attention!

# REFERENCES (1 / 2)

- ① C. Le Bris, T. Lelièvre.  
**Multiscale modelling of complex fluids: a mathematical initiation**  
*Multiscale Modeling and Simulation in Science*, 49–137, 2009
- ② M. Laso, H. Öttinger.  
**Calculation of viscoelastic flow using molecular models**  
*J Non-Newton Fluid Mech*, 47:1–20, 1993
- ③ A. Lozinski, C. Chauvière.  
**A fast solver for Fokker–Planck equation applied to viscoelastic flows calculations**  
*J Comp Phys*, 189:607–625, 2003
- ④ P. Sousa, P. Celho, M. Oliveira, M. Alves  
**Effect of the contraction ratio upon viscoelastic fluid flow in three-dimensional square–square contractions**  
*Chem Eng Sci*, 66:998–1009, 2011
- ⑤ M. Griebel, M. Schneider, C. Zenger  
**A combination technique for the solution of sparse grid problems**  
*Iterative Meth Lin Alg*, 263–281, 199



## REFERENCES (2/2)

- 6 H. Bungartz, M. Griebel, U. Rüde  
**Extrapolation, combination, and sparse grid techniques for elliptic boundary value problems**  
*Comput Meth Appl Mech Eng*, 243–252, 1994
- 7 T. Gerstner, M. Griebel  
**Numerical integration using sparse grids**  
*Numer Algorithm*, 18:209-232, 1998
- 8 T. Gerstner, M. Griebel  
**Dimension-adaptive tensor-product quadrature**  
*Comput*, 71:65-87, 2003